

# TEX

Denomination: **HIGH PERFORMANCE WOOD SCREW**

Codes: **TEXBT, TEXBP, TECBT, TEXZT, TEXZP, TEXAB**

Reference: **FT TEX-en**

Date: **13/07/18**

Revision: **5**

Page: **3 of 12**


## 2. CHARACTERISTICS

### 2.1 TEX-BT

### Yellow zinc-plated wood screw Tx recess



#### MATERIALS & GEOMETRY



Steel

Yellow  
Zinc-plated

Tx

Serrated  
S Tip

#### CHARACTERISTICS

- Yellow zinc-plated coating
- Countersunk head and y S tip.
- Tx recess
- Application: Fixing ironwork to wood, joining wood structures to each other, fixing reinforcing metal joints to wood, load-bearing wood structures.

#### BENEFITS



CE Marking

Patent

Installation with  
screwdriver

DIAMETER		Ø 4.0	Ø 4.5	Ø 5.0	Ø 6.0	Ø 8.0	Ø 10.0
dk: head diameter	[mm]	8.00	8.80	9.80	11.80	14.80	18.40
L: lengths	[mm]	16 – 70	25 – 80	30 - 120	40 – 300	80 – 400	80 – 240
D: external thread diameter	[mm]	4.0	4.5	5.0	6.0	8.0	10.0
d: inside thread diameter	[mm]	2.6	2.9	3.3	3.9	5.6	6.5
p: thread pitch	[mm]	2.30	3.6	4.0	4.6	6.2	6.8
Tx recess		T20	T20	T25	T30	T40	T40
Installation bit code		PUTO20	PUTO20	PUTO25	PUTO30	PUTO40	PUTO40

