












Kinmar® Removable Nut - Case Hardened Steel Geomet® Plated





Dimensions (mm)

| SIZE | | | | | |
|------------|------|------|------|------|------|
| DIMENSIONS | M5 | M6 | M8 | M10 | M12 |
| Α | 12.1 | 12.1 | 16.1 | 20.1 | 24.2 |
| В | 5.6 | 5.6 | 7.3 | 9.2 | 10.6 |

Material and Finish

Material: Steel C10C interannealed

Heat Treatment: Case Hardened
Finish: Geomet® 500B



Geomet® 500 is formulated with an aqueous base and is composed of Zinc and Aluminium flakes in an inorganic binder. It is chromium free. It gives protection to metalic surfaces with: barrier protection, galvanic action and passivation. Geomet® 500 was developed specifically with integral lubricant for coating fasteners, to assist in giving consistent tightening performance.

| Salt Spray (hrs) | | | |
|------------------|----------|--|--|
| White Rust | Red Rust | | |
| 240 | 1000 | | |

Part Numbers & Driver Sizes

| SIZE | M6 | M8 | M10 | M12 |
|-------------|----------|----------|----------|----------|
| PART NUMBER | KMRN06-G | KMRN08-G | KMRN10-G | KMRN12-G |
| DRIVER SIZE | KM06R | KM08R | KM10R | KM12R |

Additional Information

Patented Product: Hafren Fasteners

Installation: Kinmar® Driver Socket - see video

Removal: 2-Way Removable



Every effort has been made to ensure the accuracy of information provided in this catalogue. Hafren Fasteners cannot warrant the information however, expressly or implied, and any liability arising from it is expressly excluded. Customers must satisfy themselves as to the suitability of products and the technical information relating to them, and it is recommended that you conduct your own tests to establish suitability. All sizes shown are in mm without min and max tolerances and are guide sizes. Hafren Fasteners reserve the right to change/alter sizes without notice. This does not effect your statutory rights.