Gusseted Cantilever Arm −4X Ø13.70 -45.00±0.50 Ф -137.50±1.0*-*-WELDING-_45.0 APROX 300/1000MM #3.00±0.20 _8.0±0.20 -165.0±.1.0- \oplus \oplus 21.50-^L21.50 -355.0±1.50-MATERIAL DESCRIPTION SUPPORT (CTL) HR 3D REFERENCE HARDNESS **FINISH** DRAWING NUMBER H.D.G N/A DRAWN BY TOLERANCED:UNLESS PRORIETARY AND CONFIDENTAL ISSUE DATE UNITS J.Singh OTHERWISE SPECIFIED 02/02/2024 MM THE INFORMATION CONTAINED IN THE DRAWING IS THE SOLE PROPERTY OF UNIMETAL LTD. ANY RESPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF UNIMETAL LTD IS PROHIBITED. LINEAR DIMENSIONS ± 1.0 CHECKED BY SIZE NOT ANGULAR DIMENSIONS ± 5° IN SCALE A4 APPROVED BY HOLE TO HOLE ± 0.25 REVISION SHEET THIRD ANGLE PROJECTION 1 OF 1